SAFCO®

Performance Program

BEELINE EPU CANVAS

SOLITAIRE DOVE

FAUX FELT PEBBLE

SOLITAIRE AZTEC

BEELINE EPU SUNDANCE

GROOVE EPU CALM

ENDURANCE EPU BISQUE


FAUX FELT STONE

ENDURANCE EPU TOBACCO

GROOVE EPU BEACH

EON EPU GOLDMINE

ENDURANCE EPU CASCADE

SOLITAIRE PUMICE


ENDURANCE EPU DOVE

CANTER EPU SAFARI

CANTER EPU KIWI GREEN

ENDURANCE EPU SMITH


BEELINE EPU GEYSER

CANTER EPU SAND

COVER CLOTH PLATINUM

GROOVE EPU ARCHIVE


SOLITAIRE SMITH

EON EPU SPRING

ENDURANCE EPU AZURE

BEELINE EPU OAT


SOLITAIRE TINSEL

CANTER EPU EARTH

BEELINE EPU SPROUT

FAUX FELT SPROUT


SOLITAIRE CYAN

ENDURANCE EPU SEED

FAUX FELT GRAPHITE

COVER CLOTH TAUPE

ENDURANCE EPU SPROUT

SOLITAIRE EMERALD

COVER CLOTH CYAN

SOLITAIRE DERBY

EON EPU MINERAL

BEELINE EPU WALNUT

COVER CLOTH SORREL

CANTER EPU PINE

ENDURANCE EPU BLUEBELL

BEELINE EPU PORTOBELLO

FAUX FELT BARK

COVER CLOTH TAIGA

ENDURANCE EPU LICHEN


GROOVE EPU SURPLUS

CANTER EPU NIMBUS

CANTER EPU
ADOBE



SOLITAIRE
PEEL

ENDURANCE EPU
COPPER

ENDURANCE EPU
LAPIS

BEELINE EPU
NIMBUS

GROOVE EPU
STONE

COVER CLOTH
ZEST

CANTER EPU
TANGO

FAUX FELT
CORAL

EON EPU
FRESHWATER

CANTER EPU
BALLAD

CANTER EPU
QUARRY

BEELINE EPU
ORIOLE

EON EPU
BLAZE

COVER CLOTH
FUCHSIA

COVER CLOTH
DELFT



BEELINE EPU
TIDAL

BEELINE EPU
FORGE

ENDURANCE EPU
PAPRIKA

GROOVE EPU
INTENSE

SOLITAIRE
VIOLET

CANTER EPU
INK

EON EPU
COVE

FAUX FELT
CHARCOAL



SOLITAIRE
POPPY

CANTER EPU
SUMAC

ENDURANCE EPU
PLUM



SOLITAIRE
LAPIS

COVER CLOTH
INDIGO

ENDURANCE EPU
JETTY

CANTER EPU
RED

FAUX FELT
VIBRANT

CANTER EPU
SABLE

FAUX FELT
POOL

SOLITAIRE
GALENA

COVER CLOTH
GRAPHITE



SOLITAIRE
JUBILEE



ENDURANCE EPU
CHERRY

ENDURANCE EPU
INK



SOLITAIRE
CADET

CANTER EPU
STORM

SOLITAIRE
ONYX

ENDURANCE EPU
CLARET



BEELINE EPU
PARADE

FAUX FELT
LAGOON

FAUX FELT
QUAIL

COVER CLOTH
VESPER

CANTER EPU
ONYX

Width - Pattern	Fiber Content & Backing	Finish	Abrasion (D.R.)	Light Fastness	Approx. Repeats	Cleaning Code
54" BEELINE EPU	100% EPU Polyurethane Polyester Backing		900,000	(Cl. 4) 200 Hrs.		W BC (4:1)
54" CANTER EPU	100% EPU Polyurethane Polyester Backing		1,000,000	(Cl. 4) 200 Hrs.		W BC (4:1)
59" COVER CLOTH	56% Repreve® Post Consumer Recycled Polyester, 44% Polyester	Crypton Green®	200,000	(Cl. 4) 40 Hrs.		W BC (10:1)
54" ENDURANCE EPU	100% EPU Polyurethane Polyester Backing		1,000,000	(Cl. 4) 200 Hrs.		W BC (4:1)
54" EON EPU	100% EPU Polyurethane Polyester Backing		900,000	(Cl. 4) 200 Hrs.	5/8" L, 5/8" W	W BC (4:1)
56" FAUX FELT	62% Repreve® Post Consumer Recycled Polyester, 38% Polyester	Crypton Green®	75,000	(Cl. 4.5) 40 Hrs.		WS BC (10:1)
54" GROOVE EPU	100% EPU Polyurethane Polyester Backing		900,000	(Cl. 4) 200 Hrs.	22 1/2" L, 14 7/8" W	W BC (4:1)
57" SOLITAIRE	50% Repreve® Post Consumer Recycled Polyester, 50% Polyester	Crypton Green®	200,000	(Cl. 4) 40 Hrs.	1/8" L, 1/8" W	W BC (10:1)

*ACT ®*Registered Certification Marks*

Explanation of ACT Icons for Upholstery

Fire Retardancy

Flammability testing determines a fabric's resistance to burning. Passes Cal 117 (2013).

Colorfastness to Wet and Dry Crocking

The rubbing off of color from the fabric onto clothing, hands, or other materials and can occur under wet or dry conditions. Passes AATCC 8-1974 Dry Crocking, Class 4 minimum, Wet Crocking, Class 3 minimum.

Colorfastness to Light

The degree to which fabric will retain its color when exposed to light. Passes AATCC 16A-1974 or AATCC 16E-1976, Class 4 minimum at 40 hours.

NOTE: Class 4 minimum at 60 hours is recommended for direct sunlight exposure.

Physical Properties

Brush Pill Test to determine a fabric's pilling, Breaking/Tensile Strength Test determines the ability of a fabric to withstand tension without breaking or tearing. Seam Slippage Test determines the pulling apart of fabrics at the seams. Passes Brush Pill ASTM D3511, 3-4 minimum, Breaking Strength ASTM D3597-D1682-62 (1975) 50 lbs. minimum in warp & welt, Seam Slippage ASTM D3597-D434-75 25 lbs. minimum in warp & weft.

Abrasion

The ability of a fabric to withstand damage from wear and rubbing. Passes Heavy Duty Contract ASTM 3597 modified (No. 10 cotton duck); 30,000 double rubs Wyzenbeek Method or ASTM 4966 modified (with 21 oz. wt.) 40,000 rubs Martindale Method.

Cleaning Code

W Water-based foam or cleaner.

WS Water-based cleaning agents or foam.

BC Bleach Cleanable.

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL.COM/GG
UL 2818

GREENGUARD Certified.
CA Section 01350 compliant.
Eligible for CHPS Low-Emitting Material Credits.

SAFCO®

Safco Products Company
9300 West Research Center Road, Minneapolis, MN 55428
phone 888-971-6225/Customer Care fax 763-971-1525
Locations in Minneapolis, MN - Headquarters
Atlanta, GA, Riverside, CA and Norfolk, VA
©2021 Safco Products Company. All rights reserved.
safcoproducts.com

MOMENTUM
TEXTILES

800-366-6839
memosamples.com